

# LA8

## 2.5-Way Compact Line Array Element



- Very Compact, Lightweight
- Simple, Quick Integrated Rigging
- European Drivers for increased reliability
- 2 x 8" LF Speakers, 2 x 1" HF drivers
- Bi-Amp Operation

### OVERVIEW

The LA8 is a full-range, wide angle line array speaker designed for concert halls, nightclubs, theatre, ball-rooms and houses of worship. This line array system features an open natural sound and an exceptional 120° horizontal dispersion pattern.

The LA8 mid-low section comprises two high power 8" drivers housed in a compact, vented trapezoidal enclosure. To ensure the smoothest response in the critical mid range, the LA8 incorporates a special crossover circuit: at the lowest frequencies, both 8" drivers combine to reproduce powerful, coherent bass, while in the mid frequencies the crossover feeds only one of the two drivers. This special technique eliminates the interferences between drivers in the mid frequencies region. Besides that, this speaker is loaded by a special phase plug that widens dispersion in the horizontal coupling plane while narrowing it in the vertical non-coupling plane.

For the high frequencies the LA8 utilizes two 1" compression drivers mounted in an ICWG wave converter loaded by a 120° constant directivity wave guide.

Like the LA12, the LA8 was designed for use in groups of four or more, producing a symmetrical predictable polar pattern with a uniform power response, virtually free of comb-filtering problems.

The LA8 cabinets are constructed using 13-ply birch plywood and finished in durable black semi-matt textured paint. Front and speakers protection is assured by acoustically transparent foam and a power coated metal grille. A fast integral rigging system allows variable splay angles from 0° to 8° in 1° increments.

#### Applications

The LA8 can be used alone or combined with the LAs115

in either mobile or permanent sound installations. The LA8 is the ideal system for mid-sized applications or as downfill in larger venues.

## TECHNICAL SPECIFICATIONS

Technical Data	
Speaker Type:	Front-Loaded 2.5-Way Line Array Element
Acoustical Data	
Frequency Response (-6dB):	70Hz - 19.000Hz
Low Frequency Extension (-10dB):	64HZ
Sensitivity (1W@1m) HF:	106dB (Full-Space)
Calculated Max. SPL (Cont/Peak):	124dB/130dB (Full-Space)
Calculated Max. SPL (Cont/Peak) HF:	126dB/132dB (Full-Space)
Coverage Angle -6dB (HxV):	120° x 7°
Sensitivity (1W@1m) LF/MF:	98dB (Full-Space)
Calculated Max. SPL (Cont/Peak) LF/MF:	124dB/130dB (Full-Space)
Drivers	
Low/Mid frequency:	2 x 8" (200mm)/2" (50mm) VC, B&C custom speaker
High Frequency:	2 x 1" (25mm) exit/1.7" (65mm) VC, B&C custom compression driver
Electrical Data	
Program/Peak Power LF:	800W/1600W (10ms)
Program/Peak Power HF:	100W/200W (10ms)
Nominal Impedance HF:	16
Crossover frequency/Type (LF to MF):	250Hz (internal)
Crossover frequency/Type (MF to HF):	2250Hz Linkwitz/Riley 24dB/oct
Recommended High-Pass Filter:	60Hz, 18dB/oct Butterworth
Connectors:	2 x Neutrik NL4
Nominal Impedance LF/MF:	4 below 250Hz, 8 above 250Hz
Enclosure	
Construction:	15mm multi-laminate birch ply
Finish:	Textured black semi-matte coating
Protective grill:	Black perforated steel
Fittings:	Adjustable (0° to 8°) rigging system
Handles:	1 on each side
Dimensions (WxHxD):	801 x 250 x 336 mm
Net Weight:	28.2 kg
Shipping Weight:	29.5 kg